

Product data sheet

Specifications



Cost-effective LED Lamps - 24/48 V DC - 5W



NSYLAMT5LD1VDC

Main

Range of product	Lighting and power sockets
Accessory / separate part category	Lighting accessory
Product or component type	Lamp
Device application	Multi-purpose
Device composition	1 lamp 1 fixing elements 2 cable
Power factor	1

Complementary

Outlet standard deviation	Without socket
Rated lamp wattage	5 W
[Ue] rated operational voltage	24/48 V DC
Bulb base	Integral LED
Bulb type	LED
Control type	Built-it switch
Luminous flux	470 lm
Colour temperature	4000 K
Service life in hours	25000 h
Electrical connection	Cable quick connector 3 m supplied Cable quick connector 1 m supplied
Mounting support	Metal parts Cross rails
Fixing mode	Screws Magnetic fixing
Range compatibility	Spacial Thalassa
Length	310 mm
Height	30.5 mm
Colour	Aluminium

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Environment

IP degree of protection	IP20 conforming to IEC 60529
Electrical insulation class	Class I
Standards	IEC 60598
Ambient air temperature for operation	-10...60 °C
Ambient air temperature for storage	-16...65 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.9 cm
Package 1 Width	5.4 cm
Package 1 Length	35.0 cm
Package 1 Weight	200.0 g

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Recommended replacement(s)