

TECHNICAL SPECIFICATIONS

MODELS	CPSS7-10	CPSS7-20	CPSS7-30	CPSS7-40
INPUT				
VOLTAGE (VAC)	80-280 (L-N) / 138-485 (L-L)			
FREQUENCY (HZ)	40~70			
BYPASS VOLTAGE (VAC)	380/400/415: -20%~+15%			
POWER FACTOR	≥0.99			
THDI	≤3%			
PHASES	3:3 / 3:1 / 1:1			
OUTPUT				
POWER (KVA)	8	16	24	32
POWER FACTOR	0.8			
VOLTAGE (VAC)	L-N: 220/230/240±1% L-L: 380/400/415±1%			
FREQUENCY (HZ)	50/60±0.1			
THD	THD<1% (linear loads), THD <3% (non-linear loads)			
WAVEFORM	Sinusoidal pure, THD<1% linear			
EFFICIENCY	96%			
OVERLOAD	Constant up to 120%			
BATTERIES				
BATTERIES VOLTAGE (VDC)	±96~±240 configurable	±144~±240 configurable	±144~±240 configurable	±144~±240 configurable
MAX. CHARGING CURRENT (A)	1-10 / 1-20 (configurable)			
BATTERY LIFE	10 - 12 years			
OTHER SPECIFICATIONS				
CHARGING TIME	< 12 hours			
COMPLIANCE	Structure in compliance with CEI EN 62040			
NOISE (DB)	< 65			
TEMPERATURE (°C)	0 ~ 40			
HUMIDITY	0~95%			
DIMENSIONS (L×W×H) (MM)	250×755x880		300x785x1250	
WEIGHT (KG)	143		240	
STANDARDS AND CERTIFICATIONS	CE (Reference standards: Safety IEC EN 62040-1; EMC IEC EN 62040-2; Classification IEC EN 62040-3), EN50171			

ALL INFORMATION IS INDICATIVE, MAY BE MODIFIED BY AEC AT ANY TIME AND DOES NOT CONSTITUTE CONTRACTUAL OBLIGATIONS.

YOUTUBE VIDEO TUTORIAL



ASSISTANCE 24\7 ON ALL SOCIAL NETWORK



TECHNICAL SPECIFICATIONS						
MODELS	CPSS7-60	CPSS7-80	CPSS7-100	CPSS7-120	CPSS7-160	CPSS7-200
INPUT						
VOLTAGE (VAC)	380/400/415 (138~485 L-L)					
FREQUENCY (HZ)	40~70					
BYPASS VOLTAGE (VAC)	380/400/415: -20%~+15%					
POWER FACTOR	≥0.99					
THDI	≤3%					
PHASES	3-4W+PE					
OUTPUT						
POWER (KVA)	40	64	80	96	128	160
POWER FACTOR	0.8					
VOLTAGE (VAC)	L-N: 220/230/240±1% L-L: 380/400/415±1%					
FREQUENCY (HZ)	50/60±0.1					
THD	3-4W+PE					
WAVEFORM	Pure Sinusoidal , THD<1% linear					
EFFICIENCY	96%					
OVERLOAD	Constant at 120%					
BATTERIES						
BATTERIES VOLTAGE (VDC)	±168 ~±288 adjustable					
STANDARD BATTERY CONFIGURATION	External					
MAX. CHARGING CURRENT (A)	1-30			1-40		
BATTERY LIFE	10 - 12 years					
OTHER SPECIFICATIONS						
CHARGING TIME	< 12 hours					
COMPLIANCE	Structure in compliance with CEI EN 62040					
NOISE (DB)	<65					
TEMPERATURE (°C)	0~40					
HUMIDITY	0~95%					
DIMENSIONS (L×W×H) (MM)	450x840x1400				600x900x1600	
WEIGHT (KG)	180	210	242		320	350
STANDARDS AND CERTIFICATIONS	CE (Reference standards: Safety IEC EN 62040-1; EMC IEC EN 62040-2; Classification IEC EN 62040-3), EN50171					

ALL INFORMATION IS INDICATIVE, MAY BE MODIFIED BY AEC AT ANY TIME AND DOES NOT CONSTITUTE CONTRACTUAL OBLIGATIONS.

YOUTUBE VIDEO TUTORIAL



ASSISTANCE 24\7 ON ALL SOCIAL NETWORK

