

JUMO SIRAS P21 DP – Process Differential Pressure Transmitter with SIL (403024)

- Safety Integrity Level (SIL 2/SIL 3), PL c/PL d
- Long-term stability of < 0.1 % per year
- Linearity: 0.05 %
- HART® interface (4 user configurable measured values)
- Turn down: 1:50



Order details

(1) Basic type	
403024	JUMO SIRAS P21 DP
(2) Basic type extension	
000	None
(3) Explosion protection	
0	without explosion protection
(4) Housing	
1	Short, stainless steel, M12 connection
2	Long, stainless steel, with cable gland
3	Long, precision casting, with cable gland
(5) Electrical connection	
36	Round plug M12 × 1
93	Cable gland metal
(6) Cover material	
20	CrNi (stainless steel)
(7) Display	
1	With display (LCD)
(8) Operation	
1	With operating knob
(9) Input	
532	0 to 1 bar DP
531	-1 to 1 bar DP
533	-1 to 6 bar DP
534	-1 to 100 bar DP
(10) Output	
410	4 to 20 mA 2-wire with HART protocol
(11) Process connection	
511	1/4-18NPT DIN EN 837
(12) Process connection material	
20	CrNi (stainless steel)
(13) Filling medium measuring syst.	
01	Silicone oil
(14) Extra codes	
000	None
100	Customer-specific configuration (specifications in plain text)
624	Free from oil and grease
634	With TAG-number

Order code

(1) (2) (3) (4) (5) (6) (7) (8) (9) (10) (11) (12) (13) (14)
 / - - - - - - - - - - - /



Accessories

Description	Part no.
Line socket 4-pole, M12×1, straight, 2 m	00404585
Line socket 4-pole, M12 × 1, angled, 2 m	00409334
HART Communication Modem	00443447
Mounting bracket, Set incl. screws 7/16-	00543777
Ex-i repeater power supply and input iso amplifier 707530/38	00577948
Calibration of the mechanical measurand, pressure on site (also DAkkS)	00758363

Software

Description	Part no.
JUMO Setup SIRAS P21	00770289