

JUMO TAROS H48 Ex



Order details

(1) Basic type	
404740	JUMO TAROS H48 Ex
(2) Version	
0	Standard version
(3) Input	
464	0 to 100 bar gauge
465	0 to 160 bar gauge
511	0 to 200 bar gauge
466	0 to 250 bar gauge
517	0 to 350 bar gauge
467	0 to 400 bar gauge
468	0 to 600 bar gauge
512	0 to 800 bar gauge
469	0 to 1000 bar gauge
785	0 to 2000 psi gauge
786	0 to 3000 psi gauge
787	0 to 5000 psi gauge
788	0 to 8000 psi gauge
789	0 to 10000 psi gauge
790	0 to 15000 psi gauge
999	Special measuring range gauge
(4) Output	
405	4 to 20 mA 2-wire
(5) Process connection	
502	G 1/4 DIN EN 837
504	G 1/2 DIN EN 837
511	1/4-18NPT DIN EN 837
512	1/2-14NPT DIN EN 837
(6) Process connection material	
20	CrNi (stainless steel)
(7) Electrical connection	
36	Round plug M12 × 1
61	Line socket DIN EN 175301-803, form A
(8) Extra codes	
000	Without approval
061	With UL approval
062	With DNV approval
462	Inverted output signal
591	Throttle in pressure duct
624	Free from oil and grease
634	With TAG-number
769	With calibration certificate
871	Inspection certificate 3.1 accuracy
1160	H2 ready - mobile hydrogen applications

Order code

(1) (2) (3) (4) (5) (6) (7) (8)
 / - - - - - - -


Stock versions

Order code	Part no.
404740/0-467-405-504-20-61/061,062,1160	30072956
404740/0-465-405-504-20-61/061,062	30079410

Accessories

Description	Part no.
Magnetic pin for Teach-Function	00736330
Line socket 4-pole, M12×1, straight, 2 m	00404585
Line socket 4-pole, M12 × 1, angled, 2 m	00409334
Ex-i repeater power supply and input iso amplifier 707530/38	00577948
Calibration of the mechanical measurand, pressure on site (also DAkkS)	00758363
deployment of service	00427970
Connection cable PUR 4x0,34 BK 2000 mm with M12 connector, UL-approved	00776248
Connection cable PUR 4x0,34 BK 5000 mm with M12 connector, UL-approved	00776250
Connection cable PUR 4x0,34 BK 10000 mm with M12 connector, UL-approved	00776252