

hydroTRANS S20



Order details

(1) Basic type	
907042	JUMO hydroTRANS S20
(2) Basic type extension	
11	RH - T
12	RH - T - CO2
(3) Version	
0	Standard version
(4) Range(s)	
15	0..100 % rH/ -40..+80 °C
17	0..95 % rH/ -10..+60 °C/ 10.000 ppm
(5) Output	
009	4..20 mA/0..10 V combined output config.
530	RS485 Modbus
535	SPE with PoDL (Modbus TCP slave)
(6) Extra codes	
000	Without extra code
062	With DNV approval
775	DakKS (DKD)-calibration (as service, specify test points in plain text)
951	DAkKS-calibration (DKD), 3 test points: 20 %RH/ 50 %RH/ 80 %RH @ 23 °C
952	DAkKS-calibration (DKD), 2 test points: 33 %RH/ 76 %RH @ 23 °C
994	With integrated display

Order code

(1) (2) (3) (4) (5) (6)
 / - - - /



Single Pair Ethernet

Stock versions

Order code	Part no.
907042/11-0-15-009/000	30048052
907042/11-0-15-009/994	30048452
907042/11-0-15-530/000	30048563
907042/12-0-17-535/994	30049027
907042/11-0-15-530/994	30049446
907042/12-0-17-530/000	30049456
907042/12-0-17-530/994	30049457

Accessories

Description	Part no.
Plastic membrane filter (D = 18 mm)	30048149
PTFE-Filter (D = 18 mm)	00754581
USB cable, A connector to Micro-B connec length 3 m	00616250
4-port SPE network switch (10BASE T1L)	30062113
8-port SPE network switch (10BASE T1L)	30062447
SPE network cable 10m (with M12-connec.)	30062455
SPE network cable 5m (with M12-connec.)	30062456
SPE network cable 2m (with M12-connec.)	30062457
SPE network cable 1m (with M12-connec.)	30062458
SPE-plug according to IEC 63171-2 (IP20)	30062461
SPE-Data Cabel 2x0,35 GY schirmed	30071873

Software

Description	Part no.
Setup JUMO hydroTRANS	00775170
USB driver package for JUMO devices	30082244