

hydroTRANS S30



Order details

(1) Basic type	
907043	JUMO hydroTRANS S30
(2) Basic type extension	
11	RH - T
12	RH - T - CO2
(3) Version	
0	Standard version
(4) Range(s)	
15	0..100 % rH/ -40..+80 °C
17	0..95 % rH/ -10..+60 °C/ 10.000 ppm
(5) Output	
009	4..20 mA/0..10 V combined output config.
530	RS485 Modbus
(6) Extra codes	
000	Without extra code
062	With DNV approval
775	DakKS (DKD)-calibration (as service, specify test points in plain text)
950	Railway application
951	DAkKS-calibration (DKD), 3 test points: 20 %RH/ 50 %RH/ 80 %RH @ 23 °C
952	DAkKS-calibration (DKD), 2 test points: 33 %RH/ 76 %RH @ 23 °C
994	With integrated display

Order code

(1) (2) (3) (4) (5) (6)
 / - - - /

Stock versions

Order code	Part no.
907043/11-0-15-009/000	30049451
907043/11-0-15-530/000	30049468
907043/12-0-17-009/000	30049482
907043/12-0-17-530/000	30049485

Accessories

Description	Part no.
Plastic membrane filter (D = 18 mm)	30048149
PTFE-Filter (D = 18 mm)	00754581
USB cable, A connector to Micro-B connector length 3 m	00616250

Software

Description	Part no.
Setup JUMO hydroTRANS	00775170
USB driver package for JUMO devices	30082244