

JUMO tecLine HD Redox Combination Electrodes (201026)

- Especially robust industry electrodes for the most demanding applications
- For processes with increased pollutant and toxic loads as well as media containing oil
- For high process pressures up to 13 bar
- Wide temperature operating range up to 135 °C
- With platinum or gold tip
- With quality certificate



Order details

(1) Basic type	
201026/10	glass shaft, gel, DOKA, salt, 135°C, 13 bar
(2) Active component	
22	Platinum tip for Redox version
32	Gold tip
(3) Diaphragm	
04	PTFE ring diaphragm
11	Perforated diaphragm
(4) Connection	
82	Screw cap Pg 13,5 material PPS
(5) Insertion length	
120,00	120 mm (Standard)
225,00	225 mm
(6) Extra codes	
000	Without extra code
960	JUMO digiLine 202705, 1xRS485
961	JUMO digiLine 202705, 1xRS485, 1x4...20mA

Order code

(1)	(2)	(3)	(4)	(5)	(6)

Important information:

"The order code lists the order details and is not a modular system for individual sensor combinations. For individual combinations please consult the JUMO analytical measurement experts for prior approval."

Quantity discounts on request



Stock versions

Order code	Part no.
201026/10-22-04-82-120/000	00625340

Accessories

Description	Part no.
USB-RS485 Converter digiLine (PG203590)	00638346
JUMO DSM for JUMO digiLine incl. data ma	00663703

Software

Description	Part no.
JUMO DSM for JUMO digiLine incl. data ma	00663703
JUMO DSM Software for JUMO digiLine sens	00655787