JUMO Aquis 500 AS - Display Device / Controller for Standard Signals



- Plain language operation, multilingual
- Graphic display with background lighting
- Surface-mounted case protection type IP 67
- Calibration routine for chlorine, chlorine dioxide, ozone, hydrogen peroxide, and peracetic acid
- Voltage supply output for 2-wire transmitter according to data sheet 202630

Order details

	(1)	**Basic type**
202568/10		JUMO AQUIS 500 AS for panel-mounting
202568/20		JUMO AQUIS 500 AS wall-mount. housing
	(2)	**Input**
888		User-configurable input
	(3)	**Output 1**
000		Not to be used
888		Analog output, programmable
	(4)	**Output 2**
000		Not to be used
888		Analog output, programmable
	(5)	**Output 3**
000		Not to be used
310		Relay (changeover)
	(6)	**Output 4**
000		Not to be used
310		Relay (changeover)
	(7)	**Voltage supply**
23		AC 110 to 240 V +10/-15 %,48 to 63 Hz
25		AC/DC 20..30V,48..63Hz
30		DC 12 to 24 V +15/-15 %

Order code

(1) (2) (3) (4) (5) (6) (7)

[ ]-[ ]-[ ]-[ ]-[ ]-[ ]-[ ]

Stock versions

Order code	Part no.
202568/20-888-888-000-310-000-23/000	00528719
202568/20-888-888-888-310-310-23/000	00528718

Accessories

Description	Part no.
Protection cover for AQUIS/202610 u. Dig	00398161
Support pillar with pedestal base, arm a	00398163
Joint for suspended fitting	00453191
Mounting for DIN rails for JUMO AQUIS 50	00477842
Pipe mounting set for JUMO AQUIS 500	00483664
Rear panel set for JUMO-AQUIS 202560/65/	00506351
PC interface with converter USB/TTL	00456352
preconfiguration (Service)	00427968
deployment of service	00427970
Wartung Analysenmesstechnik	00758365

Software

Description	Part no.
Setup JUMO AQUIS 500 (PG202599)	00483602