JUMO digiLine CR HT50 – Head Transmitter with Conductive Two-Electrode Conductivity Sensor Type PK (202767)



- Bus-compatible JUMO digiLine or IO-Link interface
- JUMO digiLine interface downward compatible to Modbus RTU
- Integrated temperature compensation (automatic with Pt100, Pt1000 or manual value specification)
- Calibration possible on the transmitter or via PC in a laboratory (relative cell constant; temperature coefficient)
- Storage of calibration data and calibration logbook in JUMO digiLine electronic components
- Recording of extreme process values (drag indicator function, number/duration of limit value exceedances)
- With digital parameterization interface (JUMO DSM)

Order details

	(1)	**Basic type**
202767		JUMO digiLine CR HT50 (head transmitter with JUMO tecLine CR-PK sensor)
	(2)	**Basic type extension**
10		Digital operation plastic housing (digiLine)
15		Digital operation metal housing (digiLine)
20		Analog operation plastic housing (with analog output)
25		Analog operation metal housing (with analog output)
40		Digital operation plastic housing (IO link)
45		Digital operation metal housing (IO link)
50		Analog operation plastic housing (with solid state relay)
55		Analog operation metal housing (with solid state relay)
	(3)	**Display**
00		Without display
10		With display
	(4)	**Version**
8		Standard with default settings
9		Customer-specific configuration (specification in plain text)
	(5)	**Language**
01		German
02		English
	(6)	**Cell constant**
0001		Cell constant 0.01
0010		Cell constant 0.1
	(7)	**Measuring insert**
1003		1x Pt100 in 2-wire circuit
1005		1x Pt1000 in 2-wire circuit
	(8)	**Process connection**
997		JUMO PEKA
	(9)	**Insertion length**
40,0		Do not use! 40 mm
70,0		Do not use! 70 mm
	(10)	**Process connection material**
31		CrNi 1.4435
	(11)	**Electrode material**
31		CrNi 1.4435
	(12)	**Extra codes**
000		Without extra code
374		Inspection certificate 3.1 DIN EN 10204 material
864		Inspection certificate 3.1 material / surface roughness
955		ASTM certificate
956		FDA-Bescheinigung

Order code

(1)		(2)		(3)		(4)		(5)		(6)		(7)		(8)		(9)		(10)		(11)		(12)
	/		-		-		-		-		-		-		-		-		-		/	

Accessories

Description	Part no.
Connecting cable digiLine to AQUIS touch	00638333
Connecting cable digiLine to AQUIS touch	00638337
Connecting cable digiLine to AQUIS touch	00638341
JUMO M12-Connecting cabel 5-pol 0,5 m (P	00638312
JUMO M12-Connecting cabel 5-pol 1,5 m (P	00638313
JUMO M12-Connecting cabel 5-pol 5 m	00638315
JUMO M12-Connecting cabel 5-pol 10 m	00638322
JUMO M12-Connecting cabel 5-pol 15 m (PG	00638324
JUMO M12-Verbindungskabel 5-polig 25 m (	00720063
JUMO Y-Splitter 5pol (PG203590)	00638327
JUMO digiLine hub (PG203590)	00646871
Tube mounting set digiLine hub (PG203590	00648759
BUS termination resistor CAN- Bus/digiLi	00461591
M12 connector 8-pin straight (PG209791) by user	00444307
USB cable, A connector to Micro-B connec length 3 m	00616250
JUMO-Power Supply for digiLine hub (PG20	00661597
IO-Link Master 4 Channel	00759867
IO Link Master 8 Channel	00759875
Wartung Analysenmesstechnik	00758365
deployment of service	00427970

Software

Description	Part no.
JUMO DSM for JUMO digiLine incl. data ma	00663703
JUMO DSM Software for JUMO digiLine sens	00655787
JUMO digiLine CR/Ci IO-Link IODD V1.0.1	00734707
JUMO digiLine CR/Ci IO-Link IODD V1.1	00734708